



Product availability : Stock - Normally stocked in distribution facility



## Main

Range	TeSys
Product or component type	Contacteur
Product name	TeSys F
Device short name	LC1F
Contacteur application	Motor control Resistive load

## Complementary

Utilisation category	AC-1 AC-4 AC-3
Poles description	3P
Pole contact composition	3 NO
System Voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	250 A (<= 104 °F (40 °C)) at <= 440 V AC AC-1 150 A (<= 131 °F (55 °C)) at <= 440 V AC AC-3
Motor power kW	65 kW at 1000 V AC 50/60 Hz AC-3 75 kW at 380...400 V AC 50/60 Hz AC-3 90 kW at 500 V AC 50/60 Hz AC-3 22 kW at 400 V AC 50/60 Hz AC-4 80 kW at 415 V AC 50/60 Hz AC-3 80 kW at 440 V AC 50/60 Hz AC-3 100 kW at 660...690 V AC 50/60 Hz AC-3 40 kW at 220...240 V AC 50/60 Hz AC-3
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	250 A at <= 104 °F (40 °C)
Irms rated making capacity	1500 A AC conforming to IEC 60947-4-1

Rated breaking capacity	1200 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	1200 A <= 104 °F (40 °C) 10 s 700 A <= 104 °F (40 °C) 30 s 600 A <= 104 °F (40 °C) 1 min 450 A <= 104 °F (40 °C) 3 min 350 A <= 104 °F (40 °C) 10 min
Associated fuse rating	160 A aM at <= 440 V 250 A gG at <= 440 V
Average impedance	0.35 mOhm at 50 Hz - Ith 250 A
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power dissipation per pole	22 W AC-1 8 W AC-3
Connections - terminals	Power circuit: connector 1 cable(s) 0.19 in <sup>2</sup> (120 mm <sup>2</sup> ) Power circuit: lugs-ring terminals 1 cable(s) 0.19 in <sup>2</sup> (120 mm <sup>2</sup> ) Power circuit: bar 2 x ( 25 x 3 mm) Power circuit : bolted connection
Tightening torque	Power circuit: 159.29 lbf.in (18 N.m)
Mounting support	Plate
Mechanical robustness	Vibrations contactor closed 6 Gn, 5...300 Hz Shocks contactor open 9 Gn for 11 ms Vibrations contactor open 2 Gn, 5...300 Hz Shocks contactor closed 15 Gn for 11 ms
Height	6.69 in (170 mm)
Width	6.44 in (163.5 mm)
Depth	6.73 in (171 mm)
Product weight	8.44 lb(US) (3.83 kg)

## Environment

Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JIS C8201-4-1
Product certifications	CCC RMRoS DNV CSA ABS RINA UL CB LROS (Lloyds register of shipping)
IP degree of protection	IP2x front face with shrouds (ordered separately) conforming to IEC 60529 IP2x front face with shrouds (ordered separately) conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	23...131 °F (-5...55 °C)
Ambient air temperature for storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C)
Operating altitude	9842.52 ft (3000 m) without derating in temperature

## Ordering and shipping details

Category	22336 - CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	I12
GTIN	00785901156116
Nbr. of units in pkg.	1
Package weight(Lbs)	8.0999999999999996
Returnability	Y
Country of origin	CZ

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0843 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------