



Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	TeSys F
Range	TeSys
Product name	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Resistive load
Control circuit type	DC standard
[Uc] control circuit voltage	24 V DC
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	275 A at ≤ 104 °F (40 °C)
Rated breaking capacity	1480 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	1500 A ≤ 104 °F (40 °C) 10 s 920 A ≤ 104 °F (40 °C) 30 s 740 A ≤ 104 °F (40 °C) 1 min 500 A ≤ 104 °F (40 °C) 3 min 400 A ≤ 104 °F (40 °C) 10 min
Associated fuse rating	200 A aM at ≤ 440 V 315 A gG at ≤ 440 V
Average impedance	0.33 mOhm at 50 Hz - Ith 275 A
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power dissipation per pole	12 W AC-3 25 W AC-1
Mounting support	Plate
Standards	EN 60947-4-1 JIS C8201-4-1 IEC 60947-4-1 EN 60947-1

Product certifications	ABS LROS UL DNV CCC RMRoS CB RINA CSA
Connections - terminals	Control circuit: screw clamp terminals 2 cable(s) 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - with cable end Power circuit: connector 1 cable(s) 0.23 in ² (150 mm ²) Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in ² (1...4 mm ²) - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 2 cable(s) 0...0.01 in ² (1...4 mm ²) - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in ² (1...4 mm ²) - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in ² (1...4 mm ²) - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 2 cable(s) 0...0.01 in ² (1...4 mm ²) - cable stiffness: solid - without cable end Power circuit: lugs-ring terminals 1 cable(s) 0.23 in ² (150 mm ²) Power circuit: bar 2 x (25 x 3 mm) Power circuit : bolted connection
Tightening torque	Control circuit: 10.62 lbf.in (1.2 N.m) Power circuit: 159.29 lbf.in (18 N.m)
Operating time	30...40 ms closing 30...50 ms opening
Mechanical durability	10 Mcycles
Operating rate	2400 cyc/h at ≤ 131 °F (55 °C)

Complementary

Utilisation category	AC-1
Poles description	4P
Pole contact composition	4 NO
System Voltage	≤ 1000 V AC 50/60 Hz ≤ 460 V DC
[Ie] rated operational current	275 A (≤ 104 °F (40 °C)) at ≤ 440 V AC AC-1
Control circuit voltage limits	0.15...0.2 U _c at 131 °F (55 °C) drop-out 0.85...1.1 U _c at 131 °F (55 °C) operational
Inrush power in W	800 W at 68 °F (20 °C)
Hold-in power consumption in W	5 W at 68 °F (20 °C)
Heat dissipation	5 W

Environment

IP degree of protection	IP2x front face with shrouds (ordered separately) conforming to IEC 60529 IP2x front face with shrouds (ordered separately) conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	23...131 °F (-5...55 °C)
Ambient air temperature for storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C)
Operating altitude	9842.52 ft (3000 m) without derating in temperature
Mechanical robustness	Vibrations contactor closed 5 Gn, 5...300 Hz Shocks contactor open 7 Gn for 11 ms Vibrations contactor open 2 Gn, 5...300 Hz Shocks contactor closed 15 Gn for 11 ms
Height	6.85 in (174 mm)
Width	8.21 in (208.5 mm)
Depth	7.13 in (181 mm)

Product weight	12.02 lb(US) (5.45 kg)
----------------	------------------------

Ordering and shipping details

Category	22331 - CTR,F-LINE,DC,OPEN,NONREV
Discount Schedule	I12
Nbr. of units in pkg.	1
Package weight(Lbs)	13.220000000000001
Returnability	N
Country of origin	CZ

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------