



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Rotary Disconnects

LK4R9EM

UPC:786685409788

### Dimensions:

- **Height:** 1.8 IN
- **Length:** 2.8 IN
- **Width:** 1.3 IN

**Notes:** Each catalog number is for line or load side. For both line and load, please order two sets. For two-hole lug, consult factory.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Special Features:** 4 lugs, Cu/Al cable
- **Type:** Line or Load Terminal Lugs
- **Amperage Rating:** 400A per frame
- **Frame Size:** E-Frame
- **Main Lug Wire Size:** #2-600 kcmil per phase
- **Number Of Poles:** Four-pole
- **Series:** R9

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [LK\\_R9EM 2D Drawing Xchange](#)
- [Eaton Specification Sheet - LK4R9EM](#)
- [LK\\_R9EM AutoCAD 2D Footprint](#)
- [LK\\_R9EM 3D Inventor](#)
- [LK\\_R9EM 2D PDF](#)
- [LK\\_R9EM 3D Model Xchange](#)
- [LK\\_R9EM AutoCAD 2D Footprint \(mm\)](#)

**Certifications:** No Data

**Product compliance:** No Data



