



Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1FJ
Range compatibility	TeSys F LC1F contactor
Control circuit type	AC 40...400 Hz
[Uc] control circuit voltage	550...600 V AC 40...400 Hz
Average resistance	243 Ohm inrush at 68 °F (20 °C) 6310 Ohm holding at 68 °F (20 °C)
Inductance of closed circuit	27.4 H
Product compatibility	LC1F400
Operating time	40...75 ms closing 100...170 ms opening
Mechanical durability	10 Mcycles
Operating rate	2400 cyc/h at <= 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.85...1.1 Uc at 131 °F (55 °C) operational 40...400 Hz 0.3...0.5 Uc at 131 °F (55 °C) drop-out 40...400 Hz
Inrush power in VA	1075 VA at 68 °F (20 °C) (cos φ 0.9) 40...400 Hz
Hold-in power consumption in VA	15 VA at 68 °F (20 °C) (cos φ 0.3) 40...400 Hz
Heat dissipation	14 W at 40...400 Hz

Environment

Ambient air temperature for operation	> 23...131 °F (> -5...55 °C)
Product weight	2.2 lb(US) (1 kg)

Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	00785901445753
Nbr. of units in pkg.	1
Package weight(Lbs)	2.2000000000000002
Returnability	N
Country of origin	CZ

Contractual warranty

Warranty period	18 months
-----------------	-----------