



Powering Business Worldwide

pe.eaton.com

M22 Non-Illuminated Emergency Stop Contact Block

M22-CKC01

UPC:786685278070

Dimensions:

- **Height:** 1.54 IN
- **Length:** 1.03 IN
- **Width:** 1.18 IN

Weight:.034 LB

Notes:All NC contact blocks are positively driven contact

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Contact Block
- **Actuator:** Base, Spring-cage
- **Color:** Black
- **Contact Configuration:** NC
- **Environmental Rating:** IP65
- **Size:** 22.5 mm
- **Series:** M22

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22 Pilot Devices](#)
- [M22 Operators and Accessories](#)
- [Eaton Specification Sheet - M22-CKC01](#)
- [Global Data Sheet - M22-CKC01](#)

Certifications:

- CSA Certified
- CCC Marked



- Lloyd's Register Certified

Product compliance:

- CE Marked
- Bureau Veritas
- GoST-R

© 2016 Eaton. All rights reserved.