



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## M22 Push-Pull Emergency Stop, Complete Device

M22-PVL-K12-R

UPC:786685271828

### Dimensions:

- **Height:** 4.69 IN
- **Length:** 1.46 IN
- **Width:** 1.38 IN

**Weight:** .162 LB

**Notes:** Positively driven contact blocks.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Emergency Stop
- **Action:** Maintained
- **Actuator:** Knob, Push-pull
- **Bezel:** Silver
- **Button Color:** Red
- **Contact Configuration:** 1NO-2NC
- **Environmental Rating:** IP67, IP69K, NEMA 4X, 13
- **Illumination:** Illuminated
- **Size:** 22.5 mm
- **Series:** M22
- **Voltage Rating:** 12-30 Vac/dc

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22-PV\\_-K\\_\(3\) AutoCAD 2D Footprint](#)
- [Global Data Sheet - M22-PVL-K12-R](#)
- [M22 Operators and Accessories](#)



- [M22 Pilot Devices](#)
- [M22-PV\\_-K\\_\(3\) 2D Drawing Xchange](#)
- [Eaton Specification Sheet - M22-PVL-K12-R](#)
- [M22-PV\\_-K\\_\(3\) AutoCAD 2D Footprint \(mm\)](#)
- [M22-PV\\_-K\\_\(3\) 3D Model Xchange](#)
- [M22-PV\\_-K\\_\(3\) 3D Inventor](#)
- [M22-PV\\_-K\\_\(3\) 2D PDF](#)

**Certifications:**

- CSA Certified
- CCC Marked
- Lloyd's Register Certified

**Product compliance:**

- Bureau Veritas
- CE Marked
- GoST-R