




MGB3070-APKG/ZH

Magnetic sensors, cylinder sensors



Product characteristics

Magnetic sensor

Metal thread M18 x 1

Cable

Sensing range 70 mm; referred to magnet M4.0

Magnetic sensitivity ca. 0.8 mT

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...30 DC

Current consumption [mA]

< 10

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally closed

Voltage drop [V]

< 2.5

Current rating [mA]

200

Short-circuit protection

yes

Overload protection

yes

Switching frequency [Hz]

5000

Monitoring range

Sensing range [mm]

70, referred to magnet M4.0

Magnetic sensitivity [mT]

ca. 0.8

Accuracy / deviations

Hysteresis [% of Sr]

1...10

Environment

Ambient temperature [°C]

-25...75

Protection

IP 67

Tests / approvals

EMC

EN 61000-4-2 ESD:

4 kV CD / 8 kV AD

EN 61000-4-3 HF radiated:

10 V/m

EN 61000-4-4 Burst:

2 kV

EN 61000-4-5 Surge:

0.5 kV (line to line, Ri: 20hm)

EN 61000-4-6 HF conducted:

10 V

EN 55011:

class B

MTTF

[Years]

2630

Mechanical data

Housing materials

housing: stainless steel; active face: PBT orange; lock nuts: brass

Weight

[kg]

0.13

Displays / operating elements

Output status indication

LED

yellow

Electrical connection

Connection


PUR cable / 2 m; 3 x 0.34 mm²

Wiring

MGS202 - Magnetic sensor - eclass: 27270104 / 27-27-01-04

Core colors

BK black
BN brown
BU blue



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1