

Alternative article: MGT203

Article discontinued as of 31.March 2017

When selecting an alternative article and accessories please note that technical data may differ!


efector120

MGT200



MGK3070-BPKG/M/V4A/US-104-DPS

Magnetic sensors, cylinder sensors



Product characteristics

Magnetic sensor

Metal thread M18 x 1

Quick disconnect

Sensing range 70 mm; referred to magnet M4.0

Magnetic sensitivity 0.8 mT

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...30 DC

Current consumption [mA]

< 10

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

200

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

5000

Monitoring range

Sensing range [mm]

70, referred to magnet M4.0

Magnetic sensitivity [mT]

0.8

Accuracy / deviations

Hysteresis [% of Sr]

1...10

Environment

Ambient temperature [°C]

0...100

Protection

IP 68 / IP 69K

Tests / approvals

EMC

EN 61000-4-2 ESD: 4 kV CD / 8 kV AD
 EN 61000-4-3 HF radiated: 10 V/m
 EN 61000-4-4 Burst: 2 kV
 EN 61000-4-5 Surge: 0.5 kV (line to line, Ri: 20Ohm)
 EN 61000-4-6 HF conducted: 10 V
 EN 55011: class B

MTTF [Years]

2444

Mechanical data

Housing materials

housing: stainless steel (316L); active face: PEEK (polyether ether ketone); lock nuts: stainless steel

Weight [kg]

0.054

Displays / operating elements

Output status indication LED

yellow


MGT200 - Magnetic sensor - eclass: 27270104 / 27-27-01-04

Electrical connection

Connection

M12 connector; gold-plated contacts

Wiring



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — MGT200 — 06.01.2009

Alternative article: MGT203

Article discontinued as of 31.March 2017

When selecting an alternative article and accessories please note that technical data may differ!