

- 1: Fastening clamp
2: sensing face



Product characteristics

Cylinder sensor with GMR cell

Plastic housing for T-slot cylinders

Cable with connector

[f] flush mountable

Magnetic sensitivity 2.8 mT

Travel speed > 10 m/s

Electrical data

Electrical design

DC PNP/NPN

Operating voltage [V]

10...30 DC; cULus - Class 2 source required

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 4.5

Minimum load current [mA]

5

Leakage current [mA]

< 0.8

Current rating [mA]

100

Short-circuit protection

yes

Overload protection

yes

Switching frequency [Hz]

4000

Monitoring range

Magnetic sensitivity [mT]

2.8

Travel speed [m/s]

> 10

Accuracy / deviations

Hysteresis [mm]

1.5

Repeatability [mm]

< 0.2

Reaction times

Power-on delay time [ms]

30

Environment

Ambient temperature [°C]

-25...85

Protection

IP 65 / IP 67

Tests / approvals



EMC

EN 61000-4-2 ESD: - CD / 8 kV AD
EN 61000-4-3 HF radiated: 10 V/m
EN 61000-4-4 Burst: 2 kV
EN 61000-4-6 HF conducted: 10 V
EN 55011: class B

MK5105 - Cylinder sensor with GMR cell - eclass: 27270104 / 27-27-01-04

MTTF	[Years]	3145
UL approval number		C003
Mechanical data		
Mounting		flush mountable
Housing materials		housing: PA (polyamide); Fastening clamp: stainless steel
Weight	[kg]	0.014
Displays / operating elements		
Output status indication	LED	yellow
Electrical connection		
Connection		PUR cable / 0.3 m; with M8 connector, with turnable coupling ring

Wiring



Accessories		
Accessories (included)		rubber placeholder; cable clip
Remarks		
Remarks		Clamping screw with combined slot/hexagon socket head AF 1.5
Pack quantity	[piece]	1