

1: Fastening clamp
2: sensing face



Product characteristics

Cylinder sensor with GMR cell

Plastic housing for C-slot cylinders

Cable with connector

[f] flush mountable

Magnetic sensitivity 2.8 mT

Travel speed > 10 m/s

Electrical data

Electrical design

DC PNP

Operating voltage [V]	10...30 DC; cULus - Class 2 source required
Current consumption [mA]	< 10
Protection class	III
Reverse polarity protection	yes

Outputs

normally open

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	100
Short-circuit protection	yes
Overload protection	yes
Switching frequency [Hz]	10000

Monitoring range

Magnetic sensitivity [mT]	2.8
Travel speed [m/s]	> 10

Accuracy / deviations

Hysteresis [mm]	1.5
Repeatability [mm]	< 0.2

Reaction times

Power-on delay time [ms]	< 30
--------------------------	------

Environment

Ambient temperature [°C]	-25...85
Protection	IP 65 / IP 67

Tests / approvals

EMC

EN 61000-4-2 ESD:	- CD / 8 kV AD
EN 61000-4-3 HF radiated:	10 V/m
EN 61000-4-4 Burst:	2 kV
EN 61000-4-6 HF conducted:	10 V
EN 55011:	class B

MTTF [Years]	3731
--------------	------


UL approval number	C008
--------------------	------

Mechanical data

MK5314 - Cylinder sensor with GMR cell - eclass: 27270104 / 27-27-01-04

Mounting	flush mountable
Housing materials	housing: PA (polyamide); Fastening clamp: stainless steel
Weight [kg]	0.019
Displays / operating elements	
Output status indication LED	yellow
Electrical connection	
Connection	PUR cable / 0.3 m; with M12 connector, with turnable coupling ring

Wiring



Remarks

Pack quantity [piece]	1
-----------------------	---