



### Model Number

NCN25-30GM50-Z4

### Features

- 25 mm non-flush
- 2-wire DC
- Increased operating distance

### Accessories

#### BF 30

Mounting flange, 30 mm

## Technical Data

### General specifications

Switching element function		DC	NO
Rated operating distance	$s_n$	25 mm	
Installation		non-flush	
Output polarity		DC	
Assured operating distance	$s_a$	0 ... 20 mm	
Reduction factor $r_{Al}$		0.4	
Reduction factor $r_{Cu}$		0.4	
Reduction factor $r_{304}$		0.7	
Reduction factor $r_{Brass}$		0.5	

### Nominal ratings

Operating voltage	$U_B$	3.5 ... 30 V
Switching frequency	$f$	500 Hz
Hysteresis	$H$	typ. 3 %
Reverse polarity protection		reverse polarity-conductive
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 3.5$ V
Temperature drift		$\pm 15\%$
Operating current	$I_L$	2 ... 100 mA
Off-state current	$I_r$	typ. 0.8 mA
Switching state indicator		LED, yellow
Pre-fault indicator		LED, red
Stability control-switch point		0,8 $s_r$ ... 0,9 $s_r$

### Functional safety related parameters

MTTF <sub>d</sub>	1182 a
Mission Time (T <sub>M</sub> )	20 a
Diagnostic Coverage (DC)	0 %

### Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
Storage temperature	-25 ... 85 °C (-13 ... 185 °F)

### Mechanical specifications

Connection type	cable PVC, 2 m
Core cross-section	0.34 mm <sup>2</sup>
Housing material	brass, nickel-plated
Sensing face	PBT
Degree of protection	IP67


### Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007


### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated $\leq 36$ V

## Dimensions



## Electrical Connection



Correlation between output signal/LED-function and stable operating distance  $s_s$ /effective operating distance  $s_r$ : ( $s_s$  typ. 80 % of  $s_r$ )

