



Model Number

NCN8-18GM60-B3B-V1

Features

- Comfort series
- 8 mm non-flush
- A/B slave with extended addressing possibility for up to 62 slaves
- Cylindrical
- NO/NC selectable
- Stability control warning
- Installation help
- On/Off delay (disconnectable)
- Oscillator monitoring

Accessories

BF 18

Mounting flange, 18 mm

V1-G

Female connector, M12, 4-pin, field attachable

V1-W-2M-PUR

Female cordset, M12, 4-pin, PUR cable

V1-G-2M-PUR

Female cordset, M12, 4-pin, PUR cable

V1-W

Female connector, M12, 4-pin, field attachable

Technical Data

General specifications

Switching function		Normally open/closed (NO/NC) programmable
Output type		AS-Interface
Rated operating distance	s_n	8 mm
Installation		non-flush
Assured operating distance	s_a	0 ... 6.48 mm
Actual operating distance	s_r	7.2 ... 8.8 mm typ. 8 mm
Reduction factor r_{AI}		0.42
Reduction factor r_{CU}		0.4
Reduction factor r_{304}		0.72
Slave type		A/B slave
AS-Interface specification		V3.0
Required master specification		\geq V2.1
Output type		2-wire

Nominal ratings

Operating voltage	U_B	26.5 ... 31.9 V via AS-i bus system
Switching frequency	f	0 ... 100 Hz
Hysteresis	H	1 ... 15 typ. 5 %
Reverse polarity protection		reverse polarity protected
Voltage drop at I_L		Voltage drop $I_L = 20$ mA, switching element 3.4 ... 5 V typ. 4.3 V on U_d
Time delay before availability	t_v	\leq 1000 ms
Operating voltage indicator		dual-LED, green
Switching state indicator		dual-LED, yellow/red
Error indicator		dual-LED, red

Functional safety related parameters

MTTF _d	926 a
Mission Time (T_M)	20 a
Diagnostic Coverage (DC)	0 %

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

Storage temperature

Storage temperature	-40 ... 85 °C (-40 ... 185 °F)
---------------------	--------------------------------

Mechanical specifications

Connection type	Connector M12 x 1, 4-pin
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Degree of protection	IP67

Compliance with standards and directives


Standard conformity	
Electromagnetic compatibility	EN 50295:1999-10

Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007
-----------	---


Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated \leq 36 V

Dimensions



Electrical Connection



Pinout



Wire colors in accordance with EN 60947-5-2

1		BN	(brown)
2		WH	(white)
3		BU	(blue)
4		BK	(black)

Programming Instructions

Adress 00 preset, alterable
 via Busmaster
 or programming units

IO-Code 0
 ID-Code A
 ID1-Code 7
 ID2-Code E


Data bit

Bit	Function
D0	Switching state
D1	Prefailure message (dynamic)
D2	Oscillator monitoring
D3	Object too close

Parameter bit

Bit	Function
P0	ON / Off delay activated* / deactivated
P1	Switching element function NO* / NC
P2	not used
P3	not used

*Standard setting

Indicators

Indication depending on the distance to the object and switching element function (P1)

Distance to the object	Function	Parameter P1	yellow LED (OUT)	red LED (UAI)	Data bit D0	Data bit D3
$> 1.2 S_n$	NO	1	off	off	0	1
$1 S_n - 1.2 S_n$		1	off	flashing	0	1
$0.8 S_n - 1 S_n$		1	flashing	flashing	1	1
$0.1 S_n - 0.8 S_n$		1	on	off	1	1
$0 S_n - 0.1 S_n$		1	flashing	flashing	1	0
$> 1,2 S_n$	NC	0	on	off	1	1
$1 S_n - 1.2 S_n$		0	flashing	flashing	1	1
$0.8 S_n - 1 S_n$		0	off	flashing	0	1
$0.1 S_n - 0.8 S_n$		0	off	off	0	1
$0 S_n - 0.1 S_n$		0	off	flashing	1	0

Indication depending on the operation mode

Symptoms	green LED (POWER)	red LED (FAULT)	Data bit D2
normal operation	on	off	1
oscillator defect	flashing	flashing	0*
no communication	off	on	1

*: D0, D1, D3 will be set to 0

Dynamic pre-fault indication:

While normal operation $D1=1$. If the switch is damped critically, i.e. the object has passed uncompletely the unsafe sensing range of $0.8 S_n - 1.2 s_n$ during damping, changes $D1$ to 0 and signals that an adjustment is necessary. See the following diagram:

Monitoring "object too near":

$D3$ serves as signalling: Object too near too the sensor, danger of damage, adjustment necessary. In normal mode $D3=1$. If the object reaches the $0 - 0.1 s_n$ range, $D3=0$. If the object leaves this range, $D3=1$.

On/off delay:

The on/off delay is preset and switched on ($P0=1$). On delay approx.15 ms, when $P0=1$ and NO function ($P1=1$). Off delay approx.15 ms, when $P0=1$ and NC function ($P1=0$).