

Product characteristics

Inductive sensor

Plastic thread M30 x 1.5

Cable

ATEX approval

Group II, category 1D

Group II, category 1G/2G

Sensing range 10 mm; [f] flush mountable

Electrical data

Electrical design

Connection to certified intrinsically safe circuits with the max. values $U = 15 \text{ V} / I = 50 \text{ mA} / P = 120 \text{ mW}$

Nominal voltage [V]

8.2 DC; (1k Ω)

Supply voltage [V]

7.5...30 DC; when used outside the hazardous area

Current consumption [mA]

< 1 disabled; (> 2.1 mA enabled)

Protection class

II

Outputs

Output function

normally closed

Current rating [mA]

< 30; when used outside the hazardous area

Switching frequency [Hz]

450

Monitoring range

Sensing range [mm]

10

Real sensing range (Sr) [mm]

10 \pm 10 %

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-20...80

Protection

IP 67

Tests / approvals

Approval

PTB 01 ATEX 2191
BVS 04 ATEX E153
TIIS TC16109
IECEX BVS 06.0003

Marking of the unit

⊕ II 1G Ex ia IIB T6 Ga
⊕ II 2G Ex ia IIC T6 Gb
⊕ II 1D Ex ia IIIC T 90°C Da

EMC

EN 60947-5-6

Shock / vibration resistance

30 g (11 ms) / 10-55 Hz (1 mm)

MTTF [Years]

4963

Safety classification

Internal capacitance [nF]

< 145

Internal inductance [μ H]

< 140

NI5001 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Mechanical data


Mounting	flush mountable
Housing materials	PBT
Weight [kg]	0.174
Electrical connection	
Connection	PVC cable / 2 m; 2 x 0.5 mm ²

Wiring

Core colors

BN brown

BU blue



Accessories

Accessories (included)	2 lock nuts
Remarks	
Pack quantity [piece]	1