



Model Number

NJ15-30GK-N-150

Features

- 15 mm non-flush
- Temperature range
-25 ... 150 °C (-13 ... 302 °F)

Technical Data

General specifications

Switching function	Normally closed (NC)
Output type	NAMUR
Rated operating distance	s_n 15 mm
Installation	non-flush
Assured operating distance	s_a 0 ... 12.15 mm
Reduction factor r_{AI}	0.4
Reduction factor r_{Cu}	0.3
Reduction factor r_{304}	0.85
Output type	2-wire

Nominal ratings

Nominal voltage	U_o	8.2 V (R_i approx. 1 k Ω)
Switching frequency	f	0 ... 100 Hz

Current consumption

Measuring plate not detected	≥ 3 mA
Measuring plate detected	≤ 1 mA

Functional safety related parameters

MTTF _d	4540 a
Mission Time (T_M)	20 a
Diagnostic Coverage (DC)	0 %

Ambient conditions

Ambient temperature	-25 ... 150 °C (-13 ... 302 °F)
---------------------	---------------------------------

Mechanical specifications

Connection type	cable SIHF, 2 m
Core cross-section	0.34 mm ²
Housing material	PPS
Sensing face	PPS
Degree of protection	IP65
Cable	

Bending radius	> 10 x cable diameter
----------------	-----------------------

General information

Use in the hazardous area	see instruction manuals
Category	1G; 2G


Compliance with standards and directives

Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007


Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated ≤ 36 V

Dimensions



Electrical Connection



Equipment protection level GaCE marking **CE** 0102Effective internal inductivity C_i ≤ 140 nF ; a cable length of 10 m is considered.Effective internal inductance L_i ≤ 100 μ H ; a cable length of 10 m is considered.Highest permissible ambient temperature Details of the correlation between the type of circuit connected, the maximum permissible ambient temperature, the temperature class, and the effective internal reactance values can be found on the EU-type examination certificate.
Note: Use the temperature table for category 1 !!! The 20 % reduction in accordance with EN 1127-1 has already been applied to the temperature table for category 1.**Equipment protection level Gb**CE marking **CE** 0102Effective internal inductivity C_i ≤ 140 nF ; a cable length of 10 m is considered.Effective internal inductance L_i ≤ 100 μ H ; a cable length of 10 m is considered.Maximum permissible ambient temperature T_{amb} Details of the correlation between the type of circuit connected, the maximum permissible ambient temperature, the temperature class, and the effective internal reactance values can be found on the EU-type examination certificate.**Equipment protection level Da**CE marking **CE** 0102Effective internal inductivity C_i ≤ 140 μ F
A cable length of 10 m is considered.Effective internal inductance L_i ≤ 100 μ H
A cable length of 10 m is considered.