



Model Number

NJ6-22-N-G

Features

- 6 mm flush
- Usable up to SIL 2 acc. to IEC 61508

Technical Data

General specifications

Switching function		Normally closed (NC)
Output type		NAMUR
Rated operating distance	s_n	6 mm
Installation		flush
Assured operating distance	s_a	0 ... 4.86 mm
Reduction factor r_{AI}		0.4
Reduction factor r_{Cu}		0.3
Reduction factor r_{304}		0.85
Output type		2-wire

Nominal ratings

Nominal voltage	U_o	8.2 V (R_i approx. 1 k Ω)
Switching frequency	f	0 ... 2000 Hz
Hysteresis	H	typ. %
Current consumption		
Measuring plate not detected		≥ 3 mA
Measuring plate detected		≤ 1 mA

Functional safety related parameters

MTTF _d	4566 a
Mission Time (T_M)	20 a
Diagnostic Coverage (DC)	0 %

Ambient conditions

Ambient temperature	-25 ... 100 °C (-13 ... 212 °F)
---------------------	---------------------------------

Mechanical specifications

Connection type	cable PVC , 2 m
Core cross-section	0.75 mm ²
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Degree of protection	IP68
Cable	
Bending radius	> 10 x cable diameter

General information

Use in the hazardous area	see instruction manuals
Category	2G; 3G; 3D


Compliance with standards and directives

Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007


Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated ≤ 36 V

Dimensions



Electrical Connection



Equipment protection level Gb

CE marking	CE 0102	
Effective internal inductivity	C_i	$\leq 130 \text{ nF}$; a cable length of 10 m is considered.
Effective internal inductance	L_i	$\leq 100 \text{ }\mu\text{H}$; a cable length of 10 m is considered.
Maximum permissible ambient temperature T_{amb}	Details of the correlation between the type of circuit connected, the maximum permissible ambient temperature, the temperature class, and the effective internal reactance values can be found on the EU-type examination certificate.	

Equipment protection level Gc (ic)

CE marking	CE	
Effective internal inductivity	C_i	$\leq 130 \text{ nF}$; a cable length of 10 m is considered.
Effective internal inductance	L_i	$\leq 100 \text{ }\mu\text{H}$; A cable length of 10 m is considered.

Special conditions

for $P_i=34 \text{ mW}$, $I_i=25 \text{ mA}$, T6	55 °C (131 °F)
for $P_i=34 \text{ mW}$, $I_i=25 \text{ mA}$, T5	55 °C (131 °F)
for $P_i=34 \text{ mW}$, $I_i=25 \text{ mA}$, T4-T1	55 °C (131 °F)
for $P_i=64 \text{ mW}$, $I_i=25 \text{ mA}$, T6	55 °C (131 °F)
for $P_i=64 \text{ mW}$, $I_i=25 \text{ mA}$, T5	55 °C (131 °F)
for $P_i=64 \text{ mW}$, $I_i=25 \text{ mA}$, T4-T1	55 °C (131 °F)
for $P_i=169 \text{ mW}$, $I_i=52 \text{ mA}$, T6	41 °C (105.8 °F)
for $P_i=169 \text{ mW}$, $I_i=52 \text{ mA}$, T5	41 °C (105.8 °F)
for $P_i=169 \text{ mW}$, $I_i=52 \text{ mA}$, T4-T1	41 °C (105.8 °F)
for $P_i=242 \text{ mW}$, $I_i=76 \text{ mA}$, T6	29 °C (84.2 °F)
for $P_i=242 \text{ mW}$, $I_i=76 \text{ mA}$, T5	29 °C (84.2 °F)
for $P_i=242 \text{ mW}$, $I_i=76 \text{ mA}$, T4-T1	29 °C (84.2 °F)

Equipment protection level Da

CE marking	CE 0102	
Effective internal inductivity	C_i	$\leq 130 \text{ }\mu\text{F}$ A cable length of 10 m is considered.
Effective internal inductance	L_i	$\leq 100 \text{ }\mu\text{H}$ A cable length of 10 m is considered.

Equipment protection level Dc (tc)

CE marking	CE	
General	The corresponding datasheets, declarations of conformity, EU type examination certificates, certificates, and control drawings, where applicable (see datasheets), form an integral part of this document. These documents are available at www.pepperl-fuchs.com . The maximum surface temperature of the device was determined without a layer of dust on the apparatus. Some of the information in this instruction manual is more specific than the information provided in the datasheet.	

Special conditions

Maximum permissible ambient temperature T_{Umax}	Values can be obtained from the following list, depending on the max. operating voltage $U_{b \text{ max}}$ and the minimum series resistance R_v .	
at $U_{Bmax}=9 \text{ V}$, $R_v=562 \text{ }\Omega$	58 °C (136.4 °F)	
using an amplifier in accordance with EN 60947-	58 °C (136.4 °F)	

5-6

Release date: 2017-05-30 11:45 Date of issue: 2017-07-24 106459_eng.xml