

no longer available - archive entry Alternative article: OE0003

When selecting an alternative article and accessories please note that technical data may differ!


efector200

OE0006



OES-V/10M

Photoelectric sensors



Product characteristics

Through-beam sensor

Threaded type

M8 x 1

Cable

Transmitter

Sensing range 1m

Electrical data

Electrical design

connection to control monitors OV5012 or OV0010

Type of light

Infrared light 950 nm

Protection class

III

Reverse polarity protection

no

Outputs

Short-circuit protection

no

Overload protection

no

Monitoring range

Sensing range [m]

1

Environment

Ambient temperature [°C]

-20...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

MTTF [Years]

49633

Mechanical data

Housing materials

brass nickel-plated

Weight [kg]

0.126

Electrical connection

Connection


screened cable / 10 m; 1 x 0.14 mm²

Wiring

Core colors

RD red

screen screen



Accessories

OE0006 - Through-beam sensor - eclass: 27270901 / 27-27-09-01

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Pack quantity [piece]	1
-----------------------	---

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — OE0006 — 28.05.2013

no longer available - archive entryAlternative article: OE0003

When selecting an alternative article and accessories please note that technical data may differ!