

1: pushbutton



Product characteristics

Through-beam sensor

Rectangular, plastics

Quick disconnect

Electronic lock

Visible laser light, LASER CLASS 1

External teach function

Side sensing

Receiver

Sensing range 15m

adjustable

Electrical data

Electrical design

Operating voltage [V]

Current consumption [mA]

Type of light

Life expectancy typ. [h]

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Current rating [mA]

Short-circuit protection

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [m]

Smallest detectable object [mm]

Excess gain graphs

DC NPN

10...30 DC

< 12

red light 650 nm

50000

III

yes

light-on / dark-on programmable

< 2.5

200

yes (non-latching)


yes

1200

15


Ø 2

OJ5040 - Through-beam sensor - eclass: 27270901 / 27-27-09-01



Environment		
Ambient temperature	[°C]	-10...60
Protection		IP 67
Tests / approvals		
EMC		EN 60947-5-2
MTTF	[Years]	1005
Mechanical data		
Housing materials		housing: ABS; fixture: diecast zinc; LED window: SEPS; pushbutton: SEPS
Lens material		glass
Weight	[kg]	0.057
Displays / operating elements		
Output status indication	LED	yellow
Power	LED	green
Function display	LED	red
Electrical connection		
Connection		M8 connector

Wiring



Accessories		
Accessories (included)		Basic clip; E20964; 2 mounting screws; M3 x 16; 2 spring washers; 2 nuts
Remarks		
Remarks		cULus - Class 2 source required
Pack quantity	[piece]	1