

1: Pushbutton without function



Product characteristics

Through-beam sensor

Rectangular, plastics

Cable with connector

Front sensing

Transmitter

Sensing range 10m

Electrical data

Electrical design

Operating voltage [V]

Current consumption [mA]

Type of light

Protection class

Reverse polarity protection

Outputs

Overload protection

Monitoring range

Sensing range [m]

Light spot diameter [mm]

Environment

Ambient temperature [°C]

Protection

Tests / approvals

EMC

MTTF [Years]

Mechanical data

Housing materials

Lens material

Weight [kg]

Displays / operating elements

Power

Electrical connection

DC

10...30 DC

< 19

red light 660 nm

III

yes

yes

10

1000 (at maximum range)

-25...60

IP 67

EN 60947-5-2

1773

housing: ABS; fixture: diecast zinc; LED window: SEPS; pushbutton: SEPS; connector body: Hytrel 8068; connector thread: stainless steel 316L / 1.4404

glass


0.054

green

OJ5065 - Through-beam sensor - eclass: 27270901 / 27-27-09-01

Connection	PVC cable / 0.15 m; with M12 connector, gold-plated contacts
------------	--

Wiring



Accessories	
-------------	--

Accessories (included)	Basic clip; E20964; 2 mounting screws; M3 x 16; 2 spring washers; 2 nuts
------------------------	--

Remarks	
---------	--

Remarks	cULus - Class 2 source required
---------	---------------------------------

Pack quantity	[piece] 1
---------------	-----------