

1: Mounting on DIN rail





Product characteristics

Fiber-optic amplifier
Plastic housing
Quick disconnect
6 channels for 6 glass fiber optics Types FE-00 / FT-00
No mutual optical interference
Graphic display
Central operation
Electronic lock
Function check output
Sensing range 400mm (Through-beam sensor)
Range 0...200mm (Diffuse reflection sensor)
adjustable

Electrical data	
Electrical design	DC PNP
Operating voltage [V]	12...36 DC
Current consumption [mA]	50 (24 V)
Power consumption [VA]	1.2
Type of light	red light 630 nm
Protection class	III
Reverse polarity protection	yes
Outputs	
Output function	light-on / dark-on programmable
Voltage drop [V]	< 2
Current rating	
- Switching output [mA]	200
- Function check output [mA]	200
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	1000 typ.
Timer [s]	0.001...0.1

OO5006 - Fiber-optic amplifier - eclass: 27270905 / 27-27-09-05

Monitoring range		
Sensing range [m]		0.4 (Through-beam sensor)
Range [mm]		0...200 (Diffuse reflection sensor)
Measuring / setting range		
Possible settings		- automatic and manual switch point setting - logic functions AND; OR - second switch point
Environment		
Ambient temperature [°C]		-20...60
Protection		IP 65
Tests / approvals		
EMC		EN 60947-5-2 EN 55011: class B
Mechanical data		
Housing materials		housing: ABS; display window: PMMA; LED window: SEPS; cover: diecast zinc plastic coated (PA)
Weight [kg]		0.55
Displays / operating elements		
Display		Display unit full graphic LCD display Switching status 6 x LED yellow
Display options		- display can be rotated by 180° - language selection (German, English, French)
Electrical connection		
Connection		M16 connector
Wiring		
		 <p>E: Out 1 P: Out 2 S: Out 3 G: Out 4 C: Out 5 T: Out 6</p>
		O: function check
Accessories		
Accessories (included)		DIN rail EN60715; length: 113 mm
Remarks		
Remarks		cULus - Class 2 source required
Pack quantity [piece]		1