

- 1: potentiometer timer
- 2: potentiometer sensitivity

Receiver in upper lens, transmitter in lower lens



Product characteristics

Retro-reflective sensor

Rectangular, plastics

Terminals

Polarization filter

Sensing range 6m (Prismatic reflector Ø 80 (E20005))

adjustable

Electrical data

Electrical design

AC/DC

Operating voltage [V]

20...250 AC/DC

Type of light

red light 660 nm

Protection class

II

Reverse polarity protection

no

Outputs

Output function

light-on / dark-on programmable

Voltage drop [V]

< 10.5

Minimum load current [mA]

15

Leakage current [mA]

< 6

**Current rating**

- Current rating (continuous) [mA]

250; 350 (...50 °C)

- Current rating (peak) [mA]

î: 2.2 A (10 ms / 0.5 Hz)

Short-circuit proof

no

Overload protection

no

Switching frequency [Hz]

25

Monitoring range

Sensing range [m]

6 (Prismatic reflector Ø 80 (E20005))

Environment

Ambient temperature [°C]

-25...60

Protection

IP 65

Tests / approvals

EMC

EN 60947-5-2

MTTF [Years]

302

Mechanical data

Housing materials

modified PPO


Lens material

glass

**OS0033 - Retro-reflective sensor - eclass: 27270902 / 27-27-09-02**

Weight	[kg]	0.264
Displays / operating elements		
Output status indication	LED	yellow
Electrical connection		
Connection		terminals up to 1.5 mm <sup>2</sup> ; cable diameter 5...10 mm, cable gland M20 x 1.5

**Wiring**



Note: miniature fuse to IEC60127-2 sheet 1, ≤ 2 A (fast acting)

Accessories		
Accessories (included)		Angle bracket; E20210; screwdriver
Remarks		
Remarks		Recommendation: check the unit for reliable function after a short circuit.
Pack quantity	[piece]	1