

Receiver in lower lens, Transmitter in upper lens



Product characteristics

Retro-reflective sensor

Rectangular, plastics

Quick disconnect

Sensing range 0.15...5m (Prismatic reflector Ø 80 (E20005))
adjustable

Electrical data

Electrical design

Operating voltage [V]

Current consumption [mA]

Type of light

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Current rating [mA]

Short-circuit protection

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [m]

Light spot diameter [mm]

Excess gain graphs

DC PNP

10...50 DC

40 (24 V)

Infrared light 880 nm

II

yes

light-on / dark-on programmable

< 2.5

250

yes (non-latching)


yes

150

0.15...5 (Prismatic reflector Ø 80 (E20005))



262 (at maximum range)

OT5013 - Retro-reflective sensor - eclass: 27270902 / 27-27-09-02



Environment	
Ambient temperature [°C]	-25...60
Protection	IP 65
Tests / approvals	
EMC	EN 60947-5-2
MTTF [Years]	583
Mechanical data	
Housing materials	PBT
Lens material	PMMA
Weight [kg]	0.162
Displays / operating elements	
Output status indication LED	yellow
Power LED	green
Electrical connection	
Connection	M12 connector

Wiring



Accessories	
Accessories (included)	Angle bracket; E20461; screwdriver
Remarks	
Pack quantity [piece]	1