




OUE-HPKG

Photoelectric sensors



Receiver in upper lens



Product characteristics

Through-beam sensor

Rectangular, plastics

Cable

Receiver

Sensing range 6m

adjustable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...55 DC

Current consumption [mA]

20 (24 V)

Type of light

Infrared light 880 nm

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

light-on mode

Voltage drop [V]

< 2.5

Current rating [mA]

250

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]


140

Monitoring range

Sensing range [m]

6

Excess gain graphs




Environment

OU5007 - Through-beam sensor - eclass: 27270901 / 27-27-09-01

Ambient temperature [°C]	-25...80
Protection	IP 67
Tests / approvals	
EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	618
Mechanical data	
Housing materials	modified PPO
Lens material	glass
Weight [kg]	0.148
Displays / operating elements	
Output status indication LED	yellow
Electrical connection	
Connection	PVC cable / 2 m; 3 x 0.34 mm ²

Wiring

Core colors
 BN brown
 BU blue
 BK black



Accessories	
Accessories (included)	Angle bracket; E20211
Remarks	
Pack quantity [piece]	1