

no longer available - archive entryDiscontinued article


efector200

OU5014



OUT-HNKG

Photoelectric sensors



Receiver in upper lens, transmitter in lower lens



Product characteristics

Diffuse reflection sensor

Rectangular, plastics

Cable

Range 1...200mm (referred to white paper 200 x 200 mm)

adjustable

Electrical data

Electrical design

DC NPN

Operating voltage [V]

10...55 DC

Current consumption [mA]

35 (24 V)

Type of light

Infrared light 880 nm

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

light-on mode

Voltage drop [V]

< 2.5

Current rating [mA]

250

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

160

Monitoring range


Range [mm]

1...200 (referred to white paper 200 x 200 mm)

Light spot diameter [mm]

180 (at maximum range)

Excess gain graphs




OU5014 - Diffuse reflection sensor - eclass: 27270903 / 27-27-09-03

Environment	
Ambient temperature [°C]	-25...80
Protection	IP 67
Tests / approvals	
EMC	EN 60947-5-2
MTTF [Years]	685
Mechanical data	
Housing materials	modified PPO
Lens material	glass
Weight [kg]	0.15
Displays / operating elements	
Output status indication LED	yellow
Electrical connection	
Connection	PVC cable / 2 m; 3 x 0.34 mm ²

Wiring

Core colors
 BN brown
 BU blue
 BK black



Accessories	
Accessories (included)	Angle bracket; E20211
Remarks	
Pack quantity [piece]	1