

- 1: Aseptoflex sealing edge
2: Aseptoflex thread



EC 1935/2004 EHEDG Certified



Product characteristics
Electronic pressure sensor

Quick disconnect

no dead space

Zero and span adjustable

Programmable via EPS interface

Process connection: for Aseptoflex adapter

Analog output

Measuring range: -0.99...4.00 bar / -14.4...58.0 psi / -99...400 kPa

Application

Application

Type of pressure: relative pressure
Hygienic systems, viscous media and liquids with suspended particles
Liquids and gases

Pressure rating	30 bar	435 psi	3000 kPa
Bursting pressure min.	100 bar	1450 psi	10000 kPa
Medium temperature [°C]	-25...125 (145 max. 1h)		
Electrical data	DC		
Electrical design	DC		
Operating voltage [V]	14...30 DC ¹⁾		
Insulation resistance [MΩ]	> 100 (500 V DC)		
Protection class	III		
Reverse polarity protection	yes		
Outputs	Analog output		
Output	4...20 mA analog		
Output function	4...20 mA analog		
Overload protection	yes		
Analog output	4...20 mA		
Max. load [Ω]	max. (U _b - 13 V) / 20 mA; 550 at U _b = 24 V		
Measuring / setting range			
Measuring range	-0.99...4.00 bar	-14.4...58.0 psi	-99...400 kPa

PM2055 - Electronic pressure sensor - eclass: 27201302 / 27-20-13-02

Setting range

Analog start point, ASP	-0.99...1.00 bar	-14.4...14.5 psi	-99...100 kPa
Analog end point, AEP	0.26...4.00 bar	3.7...58.0 psi	26...400 kPa
in steps of	0.01 bar	0.1 psi	1 kPa
Factory setting	ASP = 0.00 bar; AEP = 4.00 bar		

Accuracy / deviations

Accuracy / deviations

(in % of the span) Turn down 1:1

Characteristics deviation *)	< ± 0.6
Linearity	< ± 0.5
Hysteresis	< ± 0.1
Repeatability **)	< ± 0.1
Long-term stability ***)	< ± 0.1

Temperature coefficients (TEMPCO) in the temperature range 0...80° C (in % of the span per 10 K)

Greatest TEMPCO of the zero point	< ± 0.1
Greatest TEMPCO of the span	< ± 0.2

Reaction times

Response time analog output [ms]	3
----------------------------------	---

Environment

Ambient temperature [°C]	-25...80
Storage temperature [°C]	-40...100
Protection	IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD:	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated:	10 V/m
	EN 61000-4-4 Burst:	2 kV
	EN 61000-4-6 HF conducted:	10 V

Shock resistance	DIN IEC 68-2-27:	50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6:	20 g (10...2000 Hz)
MTTF [Years]	269	



Mechanical data

Process connection	for Aseptoflex adapter	
Materials (wetted parts)	ceramics (99.9 % Al ₂ O ₃); PTFE; stainless steel 316L / 1.4404; surface characteristics: Ra < 0.4 / Rz 4	
Housing materials	stainless steel 316L / 1.4404; PEI; FPM (Viton)	
Min. pressure cycles	100 million	
Weight [kg]	0.466	

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring



Remarks

Remarks	<p>1) cULus - Class 2 source required</p> <p>*) linearity, incl. hysteresis and repeatability; (limit value setting to DIN 16086)</p> <p>***) with temperature fluctuations < 10 K</p> <p>****) in % of the span per year</p> <p>The 3-A qualification is only valid if adapters with 3-A qualification are used for installation.</p>
---------	---

Pack quantity [piece]	1
-----------------------	---