

- 1: 4-digit alphanumeric display  
2: LEDs (display unit / switching status)  
3: Programming button



Product characteristics  
Electronic pressure monitor

Quick disconnect

Function programmable

Analog input

Process connection: G 1/4 I

2 switching outputs

4-digit alphanumeric display

Measuring range: 0...25 bar

Application

Application

Type of pressure: relative pressure  
Liquids and gases

Pressure rating [bar]

100

Bursting pressure min. [bar]

350

Medium temperature [°C]

-25...80

Electrical data

Electrical design

DC PNP/NPN

Operating voltage [V]

18...30 DC

Current consumption [mA]

< 90

Insulation resistance [MΩ]

> 100 (500 V DC)

Protection class

III

Reverse polarity protection

yes

Inputs

Analog input

0...20 mA / 0...10 V

Load / input resistance [kΩ]

0...20 mA: 0.3 / 0...10 V: 90

Outputs

Output

2 switching outputs

Output function

2 x normally open / closed programmable

Current rating [mA]

250

Voltage drop [V]

< 2

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

≤ 170



Measuring / setting range

**PNI023 - Electronic pressure monitor - eclass: 27201302 / 27-20-13-02**

Display unit	bar, psi, MPa
Measuring range [bar]	0...25
Setting range	
Set point, SP [bar]	-6.2...25.0 *)
Reset point, rP [bar]	-6.3...24.9 *)
in steps of [bar]	0.1
Accuracy / deviations	
Deviations (% of value of measuring range)	
Characteristics deviation	< ± 0.6
Temperature drift ( / 10 K)	< ± 0.3
in the temperature range [°C]	0...80
Analog input	
Characteristics deviation	< ± 0.3
Temperature drift ( / 10 K)	< ± 0.1
in the temperature range [°C]	0...80
Reaction times	
Power-on delay time [s]	0.2
Min. response time switching output [ms]	3
Delay time programmable dS, dr [s]	0, 0.1...50
Damping for the switching output (dAP) [s]	0...4
Max. response time analog input [ms]	3
Integrated watchdog	yes
Software / programming	
Programming options	hysteresis / window function; N.O. / N.C; output polarity; current / voltage input; damping; calibration of displayed values; display can be rotated / deactivated; display unit
Adjustment of the switch point	Programming button
Environment	
Ambient temperature [°C]	-25...80
Storage temperature [°C]	-40...100
Protection	IP 65
Tests / approvals	
EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V
Shock resistance	DIN IEC 68-2-27: 50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6: 20 g (10...2000 Hz)
MTTF [Years]	152
Mechanical data	
Process connection	G ¼ I
Materials (wetted parts)	stainless steel (303S22); ceramics; FPM (Viton)
Housing materials	stainless steel (303S22); PBT (Pocan); PC (Makrolon); PA; FPM (Viton)
Switching cycles min.	100 million
Weight [kg]	0.292
Displays / operating elements	
Display	Display unit 3 x LED green Display mode 3 x LED green Function display 4-digit alphanumeric display Measured values 4-digit alphanumeric display
Electrical connection	
Connection	M12 connector; gold-plated contacts
<b>Wiring</b>	

**PNI023 - Electronic pressure monitor - eclass: 27201302 / 27-20-13-02**

Programming of the output function:  
 Hno = hysteresis / normally open  
 Hnc = hysteresis / normally closed  
 Fno = window function / normally open  
 Fnc = window function / normally closed



Complementary outputs:  
 output 1: = Hno, output 2: = Hnc  
 (with the same SP / rP)

Remarks

Remarks	*) differential pressure
Pack quantity [piece]	1