



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Rotary Disconnects

R5A3030U

UPC:786685402871

### Dimensions:

- Height: X
- Length: X
- Width: X

**Notes:** Suitable as motor disconnect

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Amperage Rating:** 30A
- **Fuse Configuration:** Non-fusible
- **Number Of Poles:** Three-pole
- **Product Category:** Rotary Switch
- **Series:** R5
- **Voltage Rating:** 600V

### Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)
- [Pringle Switches - Bolted contact switches](#)
- [R5A30\\_U 2D Drawing Xchange](#)
- [Eaton Specification Sheet - R5A3030U](#)
- [R5A30\\_U AutoCAD 2D Footprint \(mm\)](#)
- [R5A30\\_U AutoCAD 2D Footprint](#)
- [R5A30\\_U 3D Inventor](#)
- [R5A30\\_U 2D PDF](#)
- [R5A30\\_U 3D Model Xchange](#)

### Certifications:

- CSA Certified
- IEC Rated
- EN Listed



- UL 508

**Product compliance:**

- CCC Marked

---

© 2016 Eaton. All rights reserved.