



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Reversing solid-state contactors

**S511E10N3S**

**UPC:**782114818930

### Dimensions:

- **Height:** 3.94 IN
- **Length:** 5.04 IN
- **Width:** 1.77 IN

**Weight:**1.52 LB

**Notes:**Controller is designed for mounting in free air. If mounted horizontally, the load current must be reduced to 50% of rated current. Designed to Switch three-phase motors forward and reverse, Allows for high switching capacity.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Line Voltage:** 208-480V
- **Amperage Rating:** 10A
- **Contact Configuration:** 1NO-1NC (logic level)
- **Control Voltage:** 24-240 Vac/dc
- **Number Of Poles:** Three-pole
- **Series:** 10250T
- **Type:** 30.5 mm

### Supporting documents:

- [Eaton's Volume 6-Solid-State Motor Control](#)
- [Eaton Specification Sheet - S511E10N3S](#)

### Certifications:

- CSA Certified
- IEC 947-4-2
- UL Listed



**Product compliance:**

- CE Marked

---

© 2016 Eaton. All rights reserved.