



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Rotary Disconnects

**T5B3060U**

**UPC:**786685403007

### Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

**Notes:**Suitable as motor disconnect

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Amperage Rating:** 60A
- **Fuse Configuration:** Non-fusible
- **Number Of Poles:** Three-pole
- **Product Category:** Toggle Switch
- **Series:** R5

### Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [T5B30\\_U 2D Drawing Xchange](#)
- [Eaton Specification Sheet - T5B3060U](#)
- [T5B30\\_U AutoCAD 2D Footprint \(mm\)](#)
- [T5B30\\_U AutoCAD 2D Footprint](#)
- [T5B30\\_U 3D Inventor](#)
- [T5B30\\_U 2D PDF](#)
- [T5B30\\_U 3D Model Xchange](#)

### Certifications:

- EN Listed
- CSA Certified
- UL 508
- IEC Rated

### Product compliance:



- CCC Marked

---

© 2016 Eaton. All rights reserved.