



### Main

|                             |   |
|-----------------------------|---|
| Range of product            | Harmony XALD  |
| Product or component type   | Empty control station   |
| Device short name           | XALD  |
| Product destination         | For XB5 Ø 22 mm control and signalling units  |
| Number of cut-out           | 1 cut-out   |
| Colour of base of enclosure | Light grey RAL 7035   |
| Colour of cover             | Dark grey RAL 7016  |
| Material                    | Polycarbonate   |
| Cable entry                 | 1 knock-out for cable entry, clamping capacity: ≤ 0.55 in (14 mm)<br>2 knock-outs for Pg 13 cable gland and ISO M20, clamping capacity: ≤ 0.47 in (12 mm) |
| IP degree of protection     | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K   |

### Complementary

|                                    |   |
|------------------------------------|---|
| Assembly style                     | For customer assembly                                       |
| Number of horizontal rows          | 1   |
| Number of vertical rows            | 1   |
| Product weight                     | 0.3 lb(US) (0.136 kg)                                       |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m |
| Mounting of block                  | Front mounting<br>Rear mounting                             |
| Electrical composition code        | PF1<br>MR1<br>PF2<br>SF1<br>SF2<br>MF1<br>MF2<br>SR2<br>PR1 |

SR1

|                  |               |
|------------------|---------------|
| Main group       | 1 cut-out     |
| Group of product | Standard grey |

### Environment

|                                       |   |
|---------------------------------------|---|
| Protective treatment                  | TH  |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)  |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)  |
| Overvoltage category                  | Class II conforming to IEC 60536  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X  |
| IK degree of protection               | IK03 conforming to EN 50102   |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>UL 508<br>JIS C 4520<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5 |

### Ordering and shipping details

|                       |                       |
|-----------------------|-----------------------|
| Category              | 22475 - WALL STATIONS |
| Discount Schedule     | CS2                   |
| GTIN                  | 00785901379140        |
| Nbr. of units in pkg. | 1                     |
| Package weight(Lbs)   | 0.28999999999999998   |
| Returnability         | N                     |
| Country of origin     | FR                    |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

|                     |                          |
|---------------------|--------------------------|
| Product Life Status | END OF COMMERCIALIZATION |
|---------------------|--------------------------|