



Product availability : Stock - Normally stocked in distribution facility



### Main

Range of product	Harmony XAP
Product or component type	Die-cast empty control station
Device short name	XAPG
Product destination	For Ø 22 mm control and signalling units
Number of cut-out	2 cut-outs
Colour of base of enclosure	Grey RAL 7032
Colour of cover	Grey RAL 7032
Material	Zinc alloy
Cable entry	1 hole with blanking plug for cable gland with <= 0.55 in (14 mm) 1 hole without blanking plug for cable gland with <= 0.55 in (14 mm)
Product mounting	Flush mounting
IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010

### Complementary

Number of vertical rows	1
-------------------------	---

### Environment

Protective treatment	TC
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030

### Ordering and shipping details

Category	22475 - WALL STATIONS
----------	-----------------------

Discount Schedule	CS2
GTIN	00785901186670
Nbr. of units in pkg.	1
Package weight(Lbs)	1.1500000000000001
Returnability	N
Country of origin	MA

### Contractual warranty

Warranty period	18 months
-----------------	-----------