



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Screw Connection High Current Blocks

**XBUK150**

**UPC:**782116925483

### Dimensions:

- **Height:** 4.67 IN
- **Length:** 3.94 IN
- **Width:** 1.22 IN

**Notes:**Thread M10

### Warranties:

- 1 year

### Specifications:

- **Type:** Screw Connection
- **Amperage Rating:** IEC 309A, EN 265A, UL 285A
- **Color:** Gray
- **Enclosure Material:** Polyamide 6.6
- **Maximum Wire Size:** 300 kcmil/150 mm<sup>2</sup>
- **Quantity:** 10
- **Used With:** XBAEB231, XBMZB10
- **Voltage Rating:** IEC 1000V, EN 726V, UL 600V
- **Wire Size:** IEC #2-300 AWG, EN #2-300 AWG, UL #2 AWG-300kcmil

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [XB IEC TERMINAL BLOCKS](#)
- [XB IEC terminal blocks-versatility, quality, and reliability](#)
- [Eaton Specification Sheet - XBUK150](#)

### Certifications:

- CSA Certified
- UL Listed



**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.