



Product availability : Stock - Normally stocked in distribution facility



### Main

Device short name	XCSL
Enclosure type	Enclosure water resistant indoor/outdoor Enclosure dustproof indoor/outdoor Enclosure ice/sleet proof indoor/outdoor

### Complementary

Line Rated Current	10 A
[Us] rated supply voltage	24 V DC
Actuator	Key
Cable entry	NPT conduit entry 0.5 in
Contacts operation	Slow-break, break before make
Contacts type and composition	1 NO staggered 2 NC
Depth	1.73 in
Electrical connection	Screw clamp terminal
Enclosure material	Metal
Height	7.64 in
Installation direction	Left electromagnet connection Back actuator supply
Key locking position	Front
Locking options description	With locking of actuator, unlocking by key operated lock
Number of poles	3
Permissible voltage	<= 300 V AC
Pilot light	LED orange

### Environment

Ambient air temperature for operation	-13...158 °F
IP degree of protection	IP67

---

NEMA degree of protection	NEMA 1/2/3/4/12
---------------------------	-----------------

---

### Ordering and shipping details

---

Category	22411 - LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	00785901666929
Nbr. of units in pkg.	1
Package weight(Lbs)	1.2
Returnability	N
Country of origin	FR

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---