



Powering Business Worldwide

pe.eaton.com

XT IEC FVNR Contactor

XTCE250L22A

Dimensions:

- Height: X
- Length: X
- Width: X

Notes: Screw terminals (6-65A); 5 mm (80-150A);
no lugs (185-2000A)

Warranties: No Data

Specifications:

- **Amperage Rating:** 250A
- **Coil:** 110V 50 Hz, 120V 60 Hz
- **Contact Configuration:** 2NO-2NC
- **Frame Size:** 140 mm
- **Number Of Poles:** Three-pole
- **Terminals:** Screw terminals
- **Type:** Contactor

Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)
- [XTCE_L 2D Drawing Xchange](#)
- [XTCE_L 2D PDF](#)
- [XTCE_L AutoCAD 2D Footprint \(mm\)](#)
- [XTCE_L 3D Model Xchange](#)
- [XTCE_L 3D Inventor](#)
- [XTCE_L AutoCAD 2D Footprint](#)
- [Global Data Sheet - XTCE250L22A](#)

Certifications:

- UL Listed
- CSA Certified
- IEC 60947
- EN 60947

Product compliance:



- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.