



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## XT IEC FVNR Contactor

XTCE580N22A

### Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

**Notes:** Screw terminals (6-65A); 5 mm (80-150A);  
no lugs (185-2000A)

**Warranties:** No Data

### Specifications:

- **Amperage Rating:** 580A
- **Coil:** 110V 50 Hz, 120V 60 Hz
- **Contact Configuration:** 2NO-2NC
- **Frame Size:** 250 mm
- **Number Of Poles:** Three-pole
- **Terminals:** Screw terminals
- **Type:** Contactor

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [Global Data Sheet - XTCE580N22A](#)
- [Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)
- [XT IEC power control 580-2600A vacuum contactors](#)
- [XTCE\\_N 2D Drawing Xchange](#)
- [XTCE\\_N 2D PDF](#)
- [XTCE\\_N 3D Inventor](#)
- [XTCE\\_N 3D Model Xchange](#)
- [XTCE\\_N AutoCAD 2D Footprint](#)
- [XTCE\\_N AutoCAD 2D Footprint \(mm\)](#)

### Certifications:

- UL Listed
- CSA Certified
- IEC 60947
- EN 60947



**Product compliance:**

- CE Marked
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.