



Powering Business Worldwide

pe.eaton.com

Contactory Accessory - Auxiliary Contact

XTCEXFAC04

UPC:782116354559

Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

Notes: Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

Warranties: No Data

Specifications:

- **Mounting:** Front
- **Special Features:** Used with XTRE control relays
- **Type:** Contactory Accessory - Auxiliary Contact
- **Used With:** XTRE control relays
- **Conventional Thermal Current:** 16A
- **Contact Configuration:** 4NC
- **Number Of Poles:** Four-pole
- **Quantity:** 5
- **Rated Operational Current:** 6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
- **Terminals:** Screw terminals

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [Eaton Specification Sheet - XTCEXFAC04](#)
- [Global Data Sheet - XTCEXFAC04](#)

Certifications:

- IEC 60947



- EN 60947
- UL Listed
- CSA Certified

Product compliance:

- CCC Marked
- CE Marked
- ATEX Compliant

© 2016 Eaton. All rights reserved.