



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Contactor Accessory - Auxiliary Contact

**XTCEXFAC20**

**UPC:**786689004958

### Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

**Notes:** Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

**Warranties:** No Data

### Specifications:

- **Mounting:** Front
- **Type:** Contactor Accessory - Auxiliary Contact
- **Used With:** XTRE control relays
- **Conventional Thermal Current:** 16A
- **Contact Configuration:** 2NO
- **Number Of Poles:** Two-pole
- **Quantity:** 5
- **Rated Operational Current:** 6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
- **Terminals:** Screw terminals

### Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [Eaton Specification Sheet - XTCEXFAC20](#)
- [Global Data Sheet - XTCEXFAC20](#)

### Certifications:

- IEC 60947
- EN 60947
- UL Listed



- CSA Certified

**Product compliance:**

- CE Marked
- ATEX Compliant
- CCC Marked

---

© 2016 Eaton. All rights reserved.