



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Contactory Accessory - Auxiliary Contact

XTCEXSCC11

### Dimensions:

- Height: X
- Length: X
- Width: X

**Notes:** Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Can be mounted to the left side of contactor only. Cannot be used in combination with front (top) mount auxiliary contacts or mechanical interlocks.!

**Warranties:** No Data

### Specifications:

- **Mounting:** Side
- **Type:** Contactory Accessory - Auxiliary Contact
- **Conventional Thermal Current:** 10A
- **Contact Configuration:** 1NO-1NC
- **Frame Size:** C
- **Number Of Poles:** Two-pole
- **Quantity:** 1
- **Terminals:** Screw terminals

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [Eaton Specification Sheet - XTCEXSCC11](#)
- [Global Data Sheet - XTCEXSCC11](#)

### Certifications:

- IEC 60947
- EN 60947
- UL Listed
- CSA Certified

### Product compliance:

- CE Marked
- CCC Marked



- ATEX Compliant

---

© 2016 Eaton. All rights reserved.