



Powering Business Worldwide

pe.eaton.com

Contactory Accessory - Auxiliary Contact

XTCEXSCN11

Dimensions:

- Height: X
- Length: X
- Width: X

Notes: Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). To avoid duplicate terminal numbers in contact sequence, the XTCEXSCN11 should be used with Frame D when a top mount auxiliary is also installed.

Warranties: No Data

Specifications:

- **Mounting:** Side (snap-on)
- **Type:** Contactory Accessory - Auxiliary Contact
- **Amperage Rating:** 40-170A
- **Conventional Thermal Current:** 10A
- **Contact Configuration:** 1NO-1NC
- **Frame Size:** D-G
- **Number Of Poles:** Two-pole
- **Quantity:** 1
- **Terminals:** Screw terminals

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [Eaton Specification Sheet - XTCEXSCN11](#)
- [Global Data Sheet - XTCEXSCN11](#)

Certifications:

- IEC 60947
- EN 60947
- UL Listed
- CSA Certified

Product compliance:

- CCC Marked



- CE Marked
- ATEX Compliant

© 2016 Eaton. All rights reserved.