



Powering Business Worldwide

pe.eaton.com

## Miniature Contactor Accessory - Auxiliary Contact

XTMCXFA11

### Dimensions:

- Height: X
- Length: X
- Width: X

**Notes:** Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

**Warranties:** No Data

### Specifications:

- **Mounting:** Front
- **Type:** Miniature Contactor Accessory - Auxiliary Contact
- **Used With:** XTRM miniature control relays
- **Conventional Thermal Current:** 10A
- **Contact Configuration:** 1NO-1NC
- **Number Of Poles:** Two-pole
- **Quantity:** 5
- **Terminals:** Screw terminals

### Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [XT IEC power control 580-2600A vacuum contactors](#)
- [XTMCXFA11 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTMCXFA11](#)
- [XTMCXFA11 AutoCAD 2D Footprint](#)
- [XTMCXFA11 3D Model Xchange](#)
- [XTMCXFA11 3D Inventor](#)
- [XTMCXFA11 AutoCAD 2D Footprint \(mm\)](#)
- [Global Data Sheet - XTMCXFA11](#)

### Certifications:

- IEC 60947



- EN 60947
- UL Listed
- CSA Certified

**Product compliance:**

- ATEX Compliant
- CE Marked
- CCC Marked

---

© 2016 Eaton. All rights reserved.