



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## XT IEC Bimetallic Overload Relay

XTOB250LC1

### Dimensions:

- Height: X
- Length: X
- Width: X

**Notes:** Short-circuit Type 1 rating is 500A and short-circuit Type 2 rating is 400A for separate mounting. The main current parameters are defined by the main current wiring that is used.

**Warranties:** No Data

**Specifications:** No Data

### Supporting documents:

- [C440 Electronic Overload Relay](#)
- [Global Data Sheet - XTOB250LC1](#)
- [Eatons Volume 5-Motor Control and Protection](#)
- [XTOB\\_LC1 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTOB250LC1](#)
- [XTOB\\_LC1 AutoCAD 2D Footprint](#)
- [XTOB\\_LC1 3D Model Xchange](#)
- [XTOB\\_LC1 2D PDF](#)
- [XTOB\\_LC1 3D Inventor](#)
- [XTOB\\_LC1 AutoCAD 2D Footprint \(mm\)](#)

### Certifications:

- UL Listed
- CSA Certified
- IEC 60947
- EN 60947

### Product compliance:

- CE Marked
- RoHS Compliant
- ATEX Compliant



