



Powering Business Worldwide

pe.eaton.com

XT IEC Electronic Overload Relay

XTOE100DCS

UPC:786685416557

Dimensions:

- Height: X
- Length: X
- Width: X

Warranties: No Data

Specifications:

- **Contact Configuration:** NO-NC
- **Frame Size:** 55 mm
- **Mounting:** Direct to contactor
- **Overload Range:** 20-100A
- **Trip Type:** Selectable - 10A, 10, 20, 30

Supporting documents:

- [C440 Electronic Overload Relay](#)
- [XTOE100D_S 3D Model Xchange](#)
- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTOE/ZEB IEC Electronic Overload - Self Powered](#)
- [XTOE100D_S 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTOE100DCS](#)
- [XTOE100D_S 2D PDF](#)
- [XTOE100D_S AutoCAD 2D Footprint \(mm\)](#)
- [XTOE100D_S AutoCAD 2D Footprint](#)
- [XTOE100D_S 3D Inventor](#)

Certifications:

- CSA Certified
- IEC 60947
- EN 60947
- UL Listed

Product compliance:

- CE Marked



- RoHS Compliant
- ATEX Compliant

© 2016 Eaton. All rights reserved.