



Powering Business Worldwide

pe.eaton.com

## XT IEC Miniature Overload Relay

### XTOMP60AC1

#### Dimensions:

- Height: X
- Length: X
- Width: X

**Notes:** Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted directly to contactor.

**Warranties:** No Data

#### Specifications:

- **Contact Configuration:** 1NO-1NC
- **Frame Size:** 45 mm - mini
- **Mounting:** Direct
- **Overload Range:** 0.4-0.6A
- **Trip Type:** 10A
- **Type:** XT IEC Miniature Overload Relay

#### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [XTOM 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTOMP60AC1](#)
- [XTOM 2D PDF](#)
- [XTOM 3D Inventor](#)
- [XTOM 3D Model Xchange](#)
- [XTOM AutoCAD 2D Footprint](#)
- [XTOM AutoCAD 2D Footprint \(mm\)](#)
- [Global Data Sheet - XTOMP60AC1](#)

#### Certifications:

- UL Listed
- CSA Certified
- IEC 60947
- EN 60947



**Product compliance:**

- ATEX Compliant
- CE Marked
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.