



Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------|-----------------|
| Range of product | Harmony XAC |
| Product or component type | Selector switch |
| Component name | ZA2 |
| Product compatibility | XACA |

Complementary

| | |
|-------------------------------|------------------------|
| Marking | Unmarked |
| Cap/Operator or lens colour | Black |
| Mounting location | Front of enclosure |
| Sale per indivisible quantity | 1 |
| Product weight | 0.09 lb(US) (0.042 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60204-32 EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 100 gn conforming to IEC 60068-2-27 |
| Overvoltage category | Class II conforming to IEC 61140 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 50102 |

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 22460 - PUSHBUTTONS 22MM (PLASTIC) |
| Discount Schedule | CS2 |
| GTIN | 00785901248149 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.10000000000000001 |
| Returnability | N |
| Country of origin | MX |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|