



Main

| | |
|------------------|-------------|
| Range of product | Harmony XAC |
| Component name | XACA |

Complementary

| | |
|---------------------------------------|--|
| Marking | Unmarked |
| Cap/Operator or lens colour | Red |
| Product compatibility | XACA.. |
| Mounting location | Front of enclosure |
| Sale per indivisible quantity | 1 |
| Standards | EN/IEC 60204-32 EN/IEC 60947-5-1 EN/IEC 60947-5-5 UL 508 CSA C22.2 No 14 |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn 10...500 Hz IEC 60068-2-6 |
| Shock resistance | 100 gn IEC 60068-2-27 |
| Overvoltage category | Class II IEC 61140 |
| IP degree of protection | IP65 IEC 60529 |
| IK degree of protection | IK08 EN 50102 |
| Product weight | 0.14 lb(US) (0.065 kg) |

Ordering and shipping details

| | |
|-------------------|------------------------------------|
| Category | 22460 - PUSHBUTTONS 22MM (PLASTIC) |
| Discount Schedule | CS2 |
| GTIN | 00785901645344 |

| | |
|-----------------------|---------------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.14000000000000001 |
| Returnability | Y |
| Country of origin | FR |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

| | |
|---------------------|--------------------------|
| Product Life Status | END OF COMMERCIALIZATION |
|---------------------|--------------------------|