



### Main

Range of product	Harmony
Bezel material	Plastic
Product or component type	Head for illuminated push-button
Component name	ZA2B
Shape of signaling unit head	Round
Electrical circuit type	Control circuit
Type of operator	Spring return
Operator profile	Flush
Cap/Operator or lens colour	Blue
Marking	Unmarked

### Complementary

Mechanical durability	3000000 cycles
CAD overall width	1.18 in (30 mm)
CAD overall height	1.18 in (30 mm)
Product weight	0.03 lb(US) (0.013 kg)

### Environment

Standards	NF C 63-140 VDE 0660-200 IEC 60337-1 EN/IEC 60947-5-1
Protective treatment	TC/TH
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	15 gn (40...500 Hz) conforming to IEC 60068-2-6
Shock resistance	70 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 60536

Class II conforming to NF C 20-030

IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010
-------------------------	---

### Ordering and shipping details

Category	22460 - PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2
GTIN	00785901648468
Nbr. of units in pkg.	1
Package weight(Lbs)	0.01
Returnability	N
Country of origin	FR

### Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status

END OF COMMERCIALIZATION