



Main

Range of product	Harmony
Bezel material	Plastic
Product or component type	Head for illuminated push-button
Component name	ZA2B
Shape of signaling unit head	Round
Electrical circuit type	Control circuit
Type of operator	Spring return
Operator profile	Flush
Cap/Operator or lens colour	Clear
Marking	Unmarked

Complementary

Mechanical durability	3000000 cycles
CAD overall width	1.18 in (30 mm)
CAD overall height	1.18 in (30 mm)
Product weight	0.03 lb(US) (0.013 kg)

Environment

Standards	VDE 0660-200 EN/IEC 60947-5-1 IEC 60337-1 NF C 63-140
Protective treatment	TC/TH
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	15 gn (40...500 Hz) conforming to IEC 60068-2-6
Shock resistance	70 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 60536

Class II conforming to NF C 20-030

IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010
-------------------------	---

Ordering and shipping details

Category	22460 - PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2
GTIN	00785901248477
Nbr. of units in pkg.	1
Package weight(Lbs)	2.999999999999999E-2
Returnability	N
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status

END OF COMMERCIALIZATION