



Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|-------------------------------|--|
| Range of product | Harmony XB4 Harmony XB5 |
| Product or component type | Contact block |
| Device short name | ZBE |
| Sale per indivisible quantity | 5 |
| IP degree of protection | IP20 IEC 60529 |
| Contacts type and composition | 1 NO |
| Contact operation | Slow-break |
| Contact block type | Single |
| Contacts usage | Standard contacts |
| Connections - terminals | Screw clamp terminals $\leq 2 \times 1.5 \text{ mm}^2$ with cable end EN 60947-1 Screw clamp terminals $\geq 1 \times 0.22 \text{ mm}^2$ without cable end EN 60947-1 |

Complementary

| | |
|--------------------------|---|
| Product weight | 0.02 lb(US) (0.011 kg) |
| Positive opening | Without |
| Operating travel | 0.1 in (2.6 mm) NO changing electrical state 0.17 in (4.3 mm) total travel |
| Operating force | 2.3 N NO changing electrical state |
| Mechanical durability | 10000000 cycles |
| Tightening torque | 7.08...10.62 lbf.in (0.8...1.2 N.m) EN 60947-1 |
| Shape of screw head | Cross Philips no 1 Cross pozidriv No 1 Slotted flat Ø 4 mm Slotted flat Ø 5.5 mm |
| Contacts material | Silver alloy (Ag/Ni) |
| Short-circuit protection | 10 A cartridge fuse gG EN/IEC 60947-5-1 |

| | |
|--|---|
| [I _{th}] conventional free air thermal current | 10 A EN/IEC 60947-5-1 |
| [U _i] rated insulation voltage | 600 V 3 EN 60947-1 |
| [U _{imp}] rated impulse withstand voltage | 6 kV EN 60947-1 |
| [I _e] rated operational current | 1.2 A 600 V AC-15 A600 EN/IEC 60947-5-1 0.27 A 250 V DC-13 Q600 EN/IEC 60947-5-1 0.1 A 600 V DC-13 Q600 EN/IEC 60947-5-1 3 A 240 V AC-15 A600 EN/IEC 60947-5-1 0.55 A 125 V DC-13 Q600 EN/IEC 60947-5-1 6 A 120 V AC-15 A600 EN/IEC 60947-5-1 |
| Electrical durability | 1000000 cycles AC-15 2 A 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles DC-13 0.2 A 110 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles AC-15 3 A 120 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles AC-15 4 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles DC-13 0.5 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C |
| Electrical reliability | $\Lambda < 10\exp(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4 $\Lambda < 10\exp(-7)$ at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4 |
| Mounting of block | Front mounting |
| Condition of use | Mounting on push-button collar |
| Electrical composition code | C1 ≤ 9 C2 ≤ 7 C3 ≤ 6 C4 ≤ 4 C5 ≤ 5 C6 ≤ 3 C7 ≤ 4 C8 ≤ 2 C9 ≤ 3 C12 ≤ 6 M1 ≤ 6 M2 ≤ 4 M3 ≤ 4 M5 ≤ 2 M6 ≤ 2 M7 ≤ 6 M8 ≤ 4 M9 ≤ 2 SF1 ≤ 3 SF2 ≤ 2 MF1 ≤ 2 MF2 ≤ 2 C10 ≤ 2 M4 ≤ 2 C13 ≤ 1 |
| Compatibility code | ZBE |

Environment

| | |
|---------------------------------------|---|
| Protective treatment | TH |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C) |
| Standards | EN/IEC 60947-5-1 CSA C22.2 No 14 JIS C 4520 UL 508 EN/IEC 60947-5-4 EN/IEC 60947-1 |
| Product certifications | RINA UL GL CSA BV CCC GOST LROS (Lloyds register of shipping) DNV |
| Vibration resistance | 5 gn 2...500 Hz IEC 60068-2-6 |
| Shock resistance | 30 gn 18 ms half sine wave acceleration IEC 60068-2-27 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22469 - PUSHBUTTON,22MM ACCESSORIES-NEW |
| Discount Schedule | CS2 |
| GTIN | 00785901355632 |
| Nbr. of units in pkg. | 5 |
| Package weight(Lbs) | 0.02 |
| Returnability | Y |
| Country of origin | FR |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
