



Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKL XCKM XCKS
Associated body	ZCKS1H29 ZCKM5H29 ZCKSD39H29 ZCKLD37 ZCKMD35H29 ZCKL1H7 ZCKL7H7 ZCKMD39H29 ZCKL8H7 ZCKS1 ZCKLD39 ZCKS7 ZCKMD37H7 ZCKM6 ZCKMD31H7 ZCKM1H7 ZCKL1 ZCKS6 ZCKSD37 ZCKM7 ZCKL7 ZCKMD37H29 ZCKL6H7 ZCKS7H29 ZCKM5H7 ZCKSD31H29 ZCKL6 ZCKM6H7 ZCKL5

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKSD35
 ZCKS8
 ZCKS2H29
 ZCKMD31
 ZCKMD31H29
 ZCKM6H29
 ZCKLD35
 ZCKL8
 ZCKM8H7
 ZCKS8H29
 ZCKM7H7
 ZCKM9
 ZCKM1H29
 ZCKLD37H7
 ZCKS5H29
 ZCKLD39H7
 ZCKM5
 ZCKS2
 ZCKS5
 ZCKSD37H29
 ZCKMD39
 ZCKL5H7
 ZCKLD35H7
 ZCKLD31
 ZCKM9H29
 ZCKS6H29
 ZCKS9H29
 ZCKM7H29
 ZCKSD35H29
 ZCKSD39
 ZCKMD39H7
 ZCKM1
 ZCKSD31
 ZCKLD31H7
 ZCKMD35H7
 ZCKMD37
 ZCKM8H29
 ZCKS9
 ZCKM8
 ZCKMD35

Movement of operating head	Linear
Type of operator	Roller plunger spring return metal
Type of approach	Lateral approach 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL
Discount Schedule	T
GTIN	00785901646716
Nbr. of units in pkg.	1
Package weight(Lbs)	0.10000000000000001
Returnability	Y
Country of origin	ID

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0922 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------