



Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKM XCKS XCKL
Associated body	ZCKM6H29 ZCKS6 ZCKL7 ZCKM8H29 ZCKMD39H7 ZCKLD37 ZCKMD39 ZCKM6 ZCKM7H7 ZCKMD35 ZCKS8 ZCKSD35H29 ZCKLD31 ZCKS9 ZCKS7H29 ZCKS1H29 ZCKL1H7 ZCKM5H29 ZCKM9H29 ZCKSD37H29 ZCKMD39H29 ZCKS6H29 ZCKM6H7 ZCKSD39 ZCKS2 ZCKLD39H7 ZCKM1H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKM9
 ZCKS5
 ZCKM8H7
 ZCKL6
 ZCKLD37H7
 ZCKSD37
 ZCKM7
 ZCKS2H29
 ZCKL6H7
 ZCKM1H7
 ZCKS5H29
 ZCKLD31H7
 ZCKL1
 ZCKM5H7
 ZCKS1
 ZCKM7H29
 ZCKMD31H29
 ZCKMD35H7
 ZCKLD35H7
 ZCKL8
 ZCKSD35
 ZCKL5H7
 ZCKMD37H29
 ZCKMD35H29
 ZCKL7H7
 ZCKS7
 ZCKSD39H29
 ZCKLD39
 ZCKM1
 ZCKS8H29
 ZCKSD31H29
 ZCKLD35
 ZCKMD31
 ZCKL5
 ZCKMD31H7
 ZCKM5
 ZCKM8
 ZCKS9H29
 ZCKMD37H7
 ZCKL8H7
 ZCKMD37
 ZCKSD31

Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (with protective boot)
Type of approach	Lateral approach 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL
Discount Schedule	T
GTIN	00785901734338
Nbr. of units in pkg.	1
Package weight(Lbs)	0.12
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1014 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------