



Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKL XCKM XCKS
Associated body	ZCKM8 ZCKL8H7 ZCKM1H29 ZCKL5 ZCKL8 ZCKLD35 ZCKM8H7 ZCKM5H7 ZCKSD37 ZCKLD37H7 ZCKS9H29 ZCKMD31 ZCKS9 ZCKM5H29 ZCKLD35H7 ZCKL1H7 ZCKSD37H29 ZCKMD35H7 ZCKMD39H7 ZCKS6H29 ZCKMD35H29 ZCKS8 ZCKLD31 ZCKM7H7 ZCKMD39 ZCKL6 ZCKM8H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKM6
 ZCKM6H7
 ZCKMD31H29
 ZCKL7H7
 ZCKSD31
 ZCKSD31H29
 ZCKS2
 ZCKM6H29
 ZCKLD39H7
 ZCKM5
 ZCKMD37H29
 ZCKM7H29
 ZCKM1H7
 ZCKS8H29
 ZCKS7H29
 ZCKM7
 ZCKLD37
 ZCKS1
 ZCKMD35
 ZCKSD39
 ZCKS5
 ZCKS1H29
 ZCKSD35H29
 ZCKL6H7
 ZCKMD31H7
 ZCKLD31H7
 ZCKM1
 ZCKSD39H29
 ZCKL1
 ZCKM9
 ZCKMD39H29
 ZCKS5H29
 ZCKL7
 ZCKS6
 ZCKS2H29
 ZCKM9H29
 ZCKL5H7
 ZCKMD37
 ZCKSD35
 ZCKS7
 ZCKMD37H7
 ZCKLD39

Movement of operating head	Rotary
Type of operator	Spring rod lever spring return (with metal rod)
Type of approach	Lateral approach 2 directions

Complementary

Switch actuation	By any moving part
Positive opening	Without
Head material	Plastic

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL
Discount Schedule	T
GTIN	00785901102892
Nbr. of units in pkg.	1
Package weight(Lbs)	0.1000000000000001
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1022 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------